## **POWER WD 50 P/PD**



## **WET & DRY VACUUM CLEANERS**

Wet/dry vacuum cleaner equipped with a powerful and high efficiency New Generation motor. Model supplied with the Ultra FilteRing System (UFS) that, thanks to its special polypropylene spacer ring, allows to keep the cartridge filter (M filtration class) always installed guaranteeing best suction performances and maximum motor protection (even in case of incorrect use by the operator). UFS is also a practical solution: the floating system is independent from the motor head and fixed directly to the ring, making cleaning and maintenance guick, simple and intuitive. The PD version is equipped with a drain hose to empty the container from liquids. Exhaust air filter. Great air flow rate and suction power. Driving frame in anti-shock plastic material with accessory holders. Paper filter bag, nylon filter, HEPA cartridge filter and TNT filter optional.















wheels



Accessories holder

POWER WD 50 PD

**TYPE** POWER WD 50 P

**PRODUCT IDENTIFICATION** 

## Gangway tool (optional)

Ultra FilteRing

PTFE cartridge filter (M filtration class)

Drain hose to empty | Large diameter rear the container from liquids (PD)

TNT filter (optional)

System

REF. NO.

14581210001

15171210001

**PIECES/PALLET** 8 8

Ø <b>40</b>	
REF. NO.	
6010500	
2511606	
6010000	
6010011	
2511615	
2511610	
6730000	
2512741	
	<b>REF. NO.</b> 6010500 2511606 6010000 6010011 2511615 2511610 6730000

## **OPTIONAL ACCESSORIES**

ТҮРЕ	REF. NO.
PVC extension tube (0,5 m)	2512000
Antifoam device	6200150
Nylon filter (filtering surface 0,62 m <sup>2</sup> )	3001225
Nylon protection filter	3001016
HEPA cartridge filter (filtering surface 0,5 m <sup>2</sup> )	2512760
Paper filter bag with cap I 19 x 10	6830030
Carpet brush	2512610
TNT filter	6730015
Gangway tool	6103058

**TECHNICAL DATA** 220-240 V~ 50/60 Hz Voltage - Frequency Max power rating W 1450 W 1350 Rated power (nominal power) Container capacity 50 Useful capacity 35 Useful dust bag capacity 19 Filtering surface (textile filter) m<sup>2</sup> 0.35

		111-	0,00
	Filtering surface (cartridge filter)	m <sup>2</sup>	0,5
	Air flow rate	l/s	74
	Vacuum	mbar	260
	Noise level	db(A)	62
	IP code		IPX4
	Power supply cable	m	10
	Weight (without accessories)	Kg	14,3
	Dimensions	mm	540x490x840