

# ROUND 45 D 60

PATENTED

## WALK BEHIND SCRUBBER DRYERS ROUND 45 - WITH TRACTION

Round 45 D 60 TOUCH is the renowned Ghibli & Wirbel's scrubber dryer. The innovative and functional design guarantees the right ergonomics and comfort in the daily activities. The technical features and the high level innovations – 45 liters tank capacity, three hours running time, the control panel with display, the double brush pressure, the “silent mode” function, the new chemical mixing system – make Round 45 something unique in its market segment, ideal for effective cleaning results in every kind of floor/environment. The wide cleaning path (2 x 12” brushes) and the adjustable speed (up to 5 km/h) allow a productivity of 3050 m<sup>2</sup>/h. ROUND 45 is now available with two important upgrades:

- thanks to the new sensor TOUCH SYSTEM, Ghibli & Wirbel patented, ROUND 45 can be moved and controlled only using a thumb: intuitive, user friendly and reliable.
- ECO SYSTEM, the new program on the control panel, which optimizes consumptions, making ROUND 45 eco-friendly. Environmental care and good performance at the same time.




Control panel with display



Password for reliability and ease of use




Touch System



“Built in” solution tank filter



Debris tray + vacuum filter



Adjustable and compact squeegee



Eco System



Chemical mixing system

### PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
ROUND 45 D 60 TOUCH	10.4223.00	1
ROUND 45 D 60 BC CHEM TOUCH	17.4223.00	1

### TECHNICAL DATA

FEATURES		
Cleaning width	mm	600
Squeegee width	mm	750
Productivity (theoretical - practical)	m <sup>2</sup> /h	3050 - 1830
Power supply		Battery 24V
Installed power	W	1190
Advancement		with traction
IP code		IPX3

BATTERIES		
Type	Gel battery set (2 pcs) 12V 105Ah (*)	
Running time	h - min	2 h and 30 min
Battery compartment dimensions x No	mm x No	340x340x285 X 1

BRUSHES		
Pad diameter x No	mm - inch x No	310 - 12" x 2
Motor rating x No	W x No	450 x 1
Motor speed	rpm	200
Down pressure - Contact pressure	Kg - g/cm <sup>2</sup>	27 - 27 ; 32 - 32

TRACTION		
Motor rating	W	180
Driving speed	Km/h	5
Hill climbing ability (full load)	%	2

VACUUM		
Motor rating	W	550
Vacuum	mbar - mmH <sub>2</sub> O	1250
Airflow rating	l/s	30
Noise level	dB(A)	63/57 (**)

TANK		
Type	Double tank	
Cleaning solution tank	l	45
Recovery tank	l	47
Weight (empty/with batteries)	Kg	116 / 196
Dimensions	mm	1125x670x1040

### STANDARD ACCESSORIES

TYPE	REF. NO.
Solution tank filling hose	30.0024.00
12" Polypropylene brush ø 0.7 (***)	40.0001.00
Detachable brush deck splash guard (without bristles)	24.0266.00
Brush deck splash guard bristles	40.4007.00
Set front+rear natural rubber squeegee blades	96.0091.01
Extra weight for squeegee (1x700 g) (***)(****)	96.0171.00
Gel battery set (2 pcs) 12V 105Ah (*)	18.0001.00
On board charger 24 V 9 A (*)	22.0623.00
Chemical mixing system (*)	96.0048.00

### OPTIONAL ACCESSORIES

TYPE	REF. NO.
12" Polypropylene brush ø 0.9	40.0101.00
12" Polypropylene brush ø 1.2	40.0301.00
12" Tynex brush grit ø 1.2 grit 80	40.0201.00
Pad holder 290 mm (for 12" pad)	40.1001.00
Set front + rear polyurethane squeegee blades	96.0055.00
Fleet 4 You (*****)	96.0212.00
Fleet & Key 4 You (*****)	96.0213.00

(\*) For BC CHEM version (\*\*) Silent mode function (\*\*\*) 2 on standard equipment (\*\*\*\*) You can use maximum two weights until you reach 1400 g of total additional weight (\*\*\*\*\*) On request and to be defined at time of order