ROUND 45 SM 55



WALK BEHIND SCRUBBER DRYERS ROUND 45 - MANUAL

Round 45 SM 55 TOUCH is the scrubber dryer which has been specifically conceived for daily use. The innovative and functional design guarantees the right ergonomics and comfort in the daily activities. Cutting edge features and technical equipment make ROUND 45 SM an important point of reference in its sector, allowing the machine to be the ideal solution for effective cleaning results in every kind of floor and environment. The SM version introduces itself with top-notch innovations. • Simply Manual: a solutions system which is able to combine the best scrubbing and drying performance with an extreme ease of use: the result is a perfect mix between practicality and cost-effectiveness which guarantees the best operational performance. • TOUCH SYSTEM: the patented touch system which allows the operator to benefit from maximum flexibility and control while using the machine. Simplicity, immediacy and reliability: moving ROUND 45 with a finger has never been so practical and intuitive! ROUND 45 SM 55 TOUCH is available in three versions: one basic and two full-package which include batteries and a battery charger (up to 2 hours running time for the BC PLUS version).













Control panel

Touch System

"Built in" solution tank filter

Debris tray + vacuum filter

Compact squeegee

PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
ROUND 45 SM 55 TOUCH	10.4231.00	1
ROUND 45 SM 55 BC TOUCH	13.4231.00	1
ROUND 45 SM 55 BC PLUS TOUCH	15.4231.00	1

TECHNICAL DATA

I EURNICAL DAIA		
FEATURES		
Cleaning width	mm	530
Squeegee width	mm	750
Productivity (theoretical - practical)	m²/h	2120 - 1270
Power supply		Battery 24V
Installed power	W	750
Advancement		Manual
IP code		IPX3
BATTERIES		
Туре	Gel battery set (2 pc Gel battery set (2 pc	
Running time	h - min	1 h and 15 min (*) - 2 h (**)
Battery compartment dimensions x No BRUSHES	mm x No	340x340x285 X 1
Pad diameter x No	mm - inch x No	530 - 21" x 1
Motor rating x No	W x No	350 x 1
Motor speed	rpm	115
Down pressure - Contact pressure	Kg - g/cm ²	25,5 - 16,5
TRACTION		, ,
Motor rating	W	
Driving speed	Km/h	4
Hill climbing ability (full load)	%	2
VACUUM		
Motor rating	W	400
Vacuum	mbar - mmH ₂ 0	1189
Airflow rating	l/s	28
Noise level	dB(A)	63

TANK		
Туре		Double tank
Cleaning solution tank	1	45
Recovery tank		47
Weight (empty/with batteries)	Kg	90,5 / 143,5
Dimensions	mm	1210x560x1040

STANDARD ACCESSORIES

OTAMBAND ACCESSORIES	
TYPE	REF. NO.
Solution tank filling hose	30.0024.00
21" Polypropylene brush ø 0.7	40.0003.00
On board charger 24V 5A (*)	22.0630.00
Gel battery set (2 pcs) 12V 50A (*)	18.0026.00
On board charger 24V 9A (**)	22.0623.00
Gel battery set (2 pcs) 12V 76A (**)	18.0000.00
Set front+rear natural rubber squeegee blades	96.0091.01
Extra weight for squeegee (1x700 g) (***)	96.0171.00

OPTIONAL ACCESSORIES

TYPE	REF. NO.
21" Polypropylene brush ø 0.9	40.0103.00
21" Polypropylene brush ø 1.2	40.0303.00
21" Tynex brush ø 1.2 grit 80	40.0203.00
Pad holder 485 mm (for 20" pad)	40.1003.00
Set front + rear polyurethane squeegee blades	96.0055.00
Extra weight for squeegee (1x700 g) (***)	96.0171.00

^(*) For BC version

^(**) For BC PLUS version

^(***) You can use maximum two weights until you reach 1400 g of total additional weight