

# TOOL PRO WDA 40 H AS

## VACUUM CLEANERS FOR HAZARDOUS DUST WITH AUTOMATIC FILTER CLEANING

Large capacity, sturdy and powerful wet and dry vacuum cleaner approved for H class dust. It is specifically designed to work in high-risk environments characterized by the presence of moulds, pathogens and carcinogenic powders (such as asbestos, cobalt, nickel, lead). Compact and manageable, TOOL PRO WDA 40 H AS is ideal for use in industrial environments, craftsmen and construction sites. The innovative NONSTOPVAC! system, thanks to the automatic cleaning of the main filter through the reverse air flow, ensures a constant vacuuming and significantly reduces the downtime, allowing the operator to work without interruptions keeping high suction performance. Maximum filtration efficiency (99.995 %) thanks to the HEPA cartridge filter, installed on the machine. Equipped with the power outlet for electric tools (max power 2400 W) and COMBI Kit for connecting pneumatic accessories (optional) that ensures an operating pressure of up to 10 bar. The machine can be switched on manually or automatically (controlled by the connected tool) and it is also possible to start the vacuum cleaner directly from the flexible hose thanks to the Remote Control Kit (optional). TOOL PRO WDA 40 H AS is available with antistatic accessories supplied, to protect against any electrostatic charges that may occur during work.



Large capacity



Control panel



NONSTOPVAC!



PTFE flat filter



HEPA cartridge filter



PE bag (optional)



COMBI Kit (optional)



Antistatic accessories

### PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
TOOL PRO WDA 40 H AS	13411710001	8

### TECHNICAL DATA

Voltage - Frequency	220-240 V~	50/60 Hz
Max power rating	W	1350
Rated power (nominal power)	W	1100
Max power of electrical socket load	W	2400
Main filter	PTFE flat filter (M filtration class) + HEPA cartridge filter (H filtration class)	
Filtering surface (flat filter)	m <sup>2</sup>	0,5
Filtering surface (class H cartridge filter)	m <sup>2</sup>	0,8
Filter cleaning system	NONSTOPVAC!	
Air flow rate	l/s	76
Vacuum	mbar	250
Container capacity	l	41
Useful capacity	l	26
Useful dust bag capacity	l	20
IP code	IPX4	
Filtration class	H	
Accessories Diameter	mm	21 - 29 - 33 - 36 - 38
Power supply cable	m	7
Weight (without accessories)	Kg	21
Dimensions	mm	625x385x545

### STANDARD ACCESSORIES

TYPE	REF. NO.
Antistatic flexible hose Ø 33 - 4 m	6010530
Chromed extension tube 0,5 m (*)	2511500
Antistatic dry floor tool P340 Ø 36	6010042
Antistatic connection Ø 33	2511406
Antistatic crevice tool Ø 36	2511640
Front intake cap	2001817
PTFE flat filter (M filtration class)	2512772
HEPA cartridge filter (H filtration class)	6895010
Fleece filter bag (l 20)	---

### OPTIONAL ACCESSORIES

TYPE	REF. NO.
Antistatic flexible hose Ø 29 - 4 m	6010531
Flexible hose Ø 38 - 4 m	6010536
Squeegee tool V340 Ø 36	6010046
COMBI Kit	6689163
Remote Control Kit	6689165
Tool box adaptors	6689164
Transport handle	6340100
PE bag	3001203
Fleece filter bag l 20 x 10	3001039

(\*) 2 on standard equipment

