TOOL PRO WDA 40 L / L AS

VACUUM CLEANERS WITH AUTOMATIC FILTER CLEANING

Large capacity, sturdy and powerful wet and dry vacuum cleaner approved for L class dust. It is specifically designed to work in environments characterized by the presence of simple dust at moderate risk. Compact and manageable, TOOL PRO WDA 40 L is ideal for use in environments such as workshops and artisan laboratories. The innovative NONSTOPVAC! system, thanks to the automatic cleaning of the main filter through the reverse air flow, ensures a constant vacuuming and significantly reduces the downtime, allowing the operator to work without interruptions keeping high suction performance. Equipped with the power outlet for electric tool (max power 2400 W) and COMBI Kit for connecting pneumatic accessories (optional) that ensures an operating pressure of up to 10 bar. The machine can be switched on manually or automatically (controlled by the connected tool) and it is also possible to start the vacuum cleaner directly from the flexible hose thanks to the Remote Control Kit (optional). TOOL PRO WDA 40 L is available in two different versions: with antistatic accessories supplied (L AS version), to protect against any electrostatic charges that may occur during work, and with non-antistatic accessories (L version).





Compact and manageable



Pivoting wheels with brake



Hooks for accessories and cable holder



Power tool connection



NONSTOPVAC!

REF. NO. 13101710001



PTFE flat filter

PIECES/PALLET



Antistatic accessories (standard for L AS version)



COMBI Kit (optional)

PRODUCT IDENTIFICATION

PRODUCT IDENTIFICATION		
TYPE		
TOOL PRO WDA 40 L		
TOOL PRO WDA 40 L AS		

TECHNICAL DATA

	Voltage - Frequency	220-240 V~ 50/0	60 Hz	
	Max power rating	W	1350	
	Rated power (nominal power)	W	1100	
	Max power of electrical socket load	W	2400	
	Main filter	PTFE flat filter (M filtration class)		
	Filtering surface (flat filter)	m ²	0,5	
	Filter cleaning system		NONSTOPVAC!	
	Air flow rate	I/s	76	
	Vacuum	mbar	250	
	Container capacity		41	
	Useful capacity		26	
	Useful dust bag capacity		20	
	IP code		IPX4	
	Filtration class		L	
	Accessories Diameter	mm	33	
	Power supply cable	m	7	
	Weight (without accessories)	Kg	21	
	Dimensions	mm	625x385x545	

L	<u></u>		L



13201710001 8 STANDARD ACCESSORIES

TYPE	REF. NO.	
Flexible hose Ø 33 - 4 m (*)	6010533	
Antistatic flexible hose Ø 33 - 4 m (**)	6010530	
Chromed extension tube 0,5 m (***)	2511500	
Dry floor tool P340 Ø 36 (*)	6010041	
Antistatic dry floor tool P340 Ø 36 (**)	6010042	
Connection Ø 33 (*)	2511405	
Antistatic connection Ø 33 (**)	2511406	
Crevice tool Ø 36 (*)	2511520	
Antistatic crevice tool Ø 36 (**)	2511640	
Front intake cap	2001817	
PTFE flat filter (M filtration class)	2512772	
Fleece filter bag (I 20)		

OPTIONAL ACCESSORIES

OI HOMAE AUGESSOINES			
TYPE	REF. NO.		
Antistatic flexible hose Ø 29 - 4 m (**)	6010531		
Flexible hose Ø 38 - 4 m	6010536		
Squeegee tool V340 Ø 36	6010046		
COMBI Kit	6689163		
Remote Control Kit	6689165		
Tool box adaptors	6689164		
Transport handle	6340100		
PE bag	3001203		
Fleece filter bag I 20 x 10	3001039		

(*) For L version (**) For L AS version (***) 2 on standard equipment